
A STATE OF THE STA

The Files
tober 1954
Contract PSC-148-UNV - Trip Report

1. A visit was made to the Chicago, Illinois, 29 September 1974, to inspect power output figures for the RT-6A transmitter, as modified.

2. Those present for discussions of the modified RT-6A were:



- 3. The purpose of the visit was to examine power output tables of a production run of 24 RT-6A units, as modified, to determine if the degree of increased power output as a result of the modification was sufficient to justify increased costs not to exceed \$4.00 per unit. had indicated in a phone conversation that the power increase was approximately 15%. A 15% power increase for modified equipment was not considered satisfactory.
- the New power output minimums were selected on the basis of complete power output tests made on 24 transmitters. These data are presented in bar-graphs and are attached. The AC Operation bar-graphs are accompanied by a similar bar-graph of the unmodified RT-6A for comparison. Please note that the "new" and "old" graphs are drawn to different scales.
- 5. The new minimum power output table represents an average of 33% increase in power output over the previously authorized table. The power increase above the minimum power output requirements ranges between 33% and 10% for points checked.
- 6. Twenty-five RT-6A equipments were modified for power output tests. It should be noted that 23 of these sets were subjected to the tests "as is". The 24th unit was included in the tests after the 2E26 had been replaced because of excessive plate current. The performance of the 25th unit was below that of the 24 units and was excluded from further tests. Stated that the 25th unit required a new oscillator and amplifier and now performed satisfactorily.



25X1

25X1

25X1

25X1

25X1

25**X**1

20/(1

25X1

Sanitized Copy Approved for Release 2011/09/20 : CIA-RDP78-03424A002400020017-7

CONFIDENTIÁL

Subject: Contrac	: PSC-11:8-UW	1774	Trip	Report	(Cont'd)	1
------------------	---------------	------	------	--------	----------	---

4 October 1950

7. The Navy inspectors were queried as to their tests of the modified equipment and no negative comment was received, the Naval inspector, stated that the rejection rate had been and continues to be about \$35. This was not verified.
3. The modification physically includes a new tank coil of reduced binensions. The quality of construction is excellent. The coil is tapped for two band operation. The low band L has a non-adjustable iron slug and includes the high band turns in series. High band operation grounds the low and L. The modification also requires the removal of 5 plates from the cank condenser, the removal of the RF choke, two leads, and the removal of a condenser.
phoned the new power table figures to and the undersigned recommended acceptance on the basis that the RT-6A now looks like a good solid 9 watt (nominal) transmitter.

Attachments: Power Bar-graphs New Power Table

R&D-EP/CEM/mlk 4 Oct 1954

cc: Subject (Monthly Dev

CONFIDENTIAL

25X1

25X1

25X1